

LF 3000: Polymer Push-In Fittings - Stecker

-20 °C bis +80 °C  
20 bar Höchstdruck (Vakuum 755 mmHg)

3102 Gleichschenkeliger Winkel



Neu

ØD	Bestellnummer
4	3102 04 00
6	3102 06 00
8	3102 08 00
10	3102 10 00
12	3102 12 00
14	3102 14 00
16	3102 16 00

3140 Einzel-Y-Verbinder - gleich- und ungleichschenkelig



ØD1	ØD2	Bestellnummer
4	4	3140 04 00
4	6	3140 04 06
6	6	3140 06 00
6	8	3140 06 08
8	8	3140 08 00

3104 T-Stück - gleich- und ungleichschenkelig



Neu

ØD1	ØD2	Bestellnummer
4	4	3104 04 00
4	6	3104 04 06
6	4	3104 06 04
6	6	3104 06 00
6	8	3104 06 08
8	6	3104 08 06
8	8	3104 08 00
8	10	3104 08 10
10	8	3104 10 08
10	10	3104 10 00
10	12	3104 10 12
12	10	3104 12 10
12	12	3104 12 00
14	8	3104 14 08
14	14	3104 14 00
16	16	3104 16 00
16	12	3104 16 12

3144 Mehrfach-Y-Verbinder - gleich- und ungleichschenkelig



ØD1	ØD2	Bestellnummer
4	4	3144 04 04
4	6	3144 04 06
6	6	3144 06 06
6	8	3144 06 08

3304 Ungleichschenkeliges Mehrfach-T-Stück



ØD1	ØD2	Bestellnummer
6	4	3304 06 04
8	4	3304 08 04
8	6	3304 08 06
10	6	3304 10 06
10	8	3304 10 08

3106 Rohr/Rohrstecker - gleich- und ungleichschenkelig



Neu

ØD1	ØD2	Bestellnummer
4	4	3106 04 00
4	6	3106 04 06
4	8	3106 04 08
6	6	3106 06 00
6	8	3106 06 08
6	10	3106 06 10
8	8	3106 08 00
8	10	3106 08 10
8	12	3106 08 12
10	10	3106 10 00
10	12	3106 10 12
12	12	3106 12 00
12	14	3106 12 14
14	14	3106 14 00
16	16	3106 16 00
16	12	3106 16 12

3306 Ungleichschenkeliger Mehrfachwinkel



ØD1	ØD2	Bestellnummer
6	4	3306 06 04
8	4	3306 08 04
8	6	3306 08 06
10	6	3306 10 06
10	8	3306 10 08

3107 Kreuzverbinder - gleich- und ungleichschenkelig



ØD1	ØD2	Bestellnummer
4	4	3107 04 00
4	6	3107 04 06
6	6	3107 06 00
6	8	3107 06 08
8	8	3107 08 00