



Pneumatic Catalogue

Quick Coupling Systems for Pneumatic and Fluid Handling



ENGINEERING YOUR SUCCESS.

Nominal Diameter**7,8** = 48 mm²**Rectus Series****1625**

Premium industrial coupling 3/8" with European standard profile. Suitable for compressed air applications with greater than average air consumption. Coupling system with single-hand operation. Ultra High Flow valve for optimum flow and low pressure drop. Extremely robust and ergonomically shaped, 2-component plastic sleeve.

Series 1625 with additional end connections available on request.

Dust Protections (P. 250)
for Coupling Part.-No. SK23S
for Plug Part.-No. SK12S

Working Temperature*

-20°C up to +40°C (NBR)
depending on the medium.

* For temperatures below -20°C and over +40°C and depending on the medium, other seal variants (FKM, EPDM, FFKM) are available.

**Working Pressure****

35 bar

** maximum static working pressure with design factor 4 to 1.

Material

Coupling: Brass nickel plated,
Steel QPQ treated, PA6+TPE

Plug: Steel zinc plated

Seals: NBR

Technical Description

Connecting Force 0 bar: 30 N


Connecting Force 6 bar: 75 N

Vacuum Coupling: 87%

Vacuum connected: 87%

Interchangeability (KA only)




- Rectus 25 + 26
- Rectus 1600
- Cejn 320
- JWL 520 + JWL 530
- various German Products

Flow diagrams**Air**



Coupling – with valve




Series 1625KA

Connection A	HEX mm	L mm	L1 mm	D mm	Part Number
	R 1/4 R 3/8 R 1/2	19 19 22	65 65 59,5	12 12 17	26 26 26
Male Thread					
	G 1/4 G 3/8 G 1/2	19 19 24	59 59 62	9 9 12	26 26 26
Female Thread					
	6 mm 8 mm 9 mm 10 mm 13 mm	19 19 19 19 19	80 80 80 80 80	25 25 25 25 25	26 26 26 26 26
Hose Barb					



Plugs – without valve

Series 25SF

Connection A	HEX mm	L mm	L1 mm	D mm	Part Number
	R 1/8 R 1/4 R 3/8 R 1/2	13 14 17 22	33 37 37 43	9 12 12 17	25SFAK10SXZ 25SFAK13SXZ 25SFAK17SXZ 25SFAK21SXZ
Male Thread					
	G 1/8 G 1/4 G 3/8 G 1/2	14 17 19 24	30 38,5 39,5 44	7 9 9 12	25SFIW10SXZ 25SFIW13SXZ 25SFIW17SXZ 25SFIW21SXZ
Female Thread					
	6 mm 8 mm 9 mm 10 mm 13 mm		48 48 48 48 48	25 25 25 25 25	12 12 12 12 15
Hose Barb					

 Please consider our security advices on the pages 12/13 