

Feature	Code	Description
SERIES	PVQ	INLINE PISTON PUMP, VARIABLE VOLUME, QUIET SERIES
DISPLACEMENT	32	32.9 CC/REV (2.01 CIR), 140 BAR (2000 PSI)
MOUNTING FLANGE	-B2	FLANGE SAE J744 101-2 (SAE-B)
INPUT SHAFT ROTATION	R	RIGHT-HAND ROTATION (CW)
THRU-DRIVE WITHOUT COUPLING	-	NO THRU-DRIVE
PORTS - TYPE AND LOCATION	-SE	STANDARD - INCH O-RING BOSS, 1.625" INLET AND OUTLET, END PORT
SHAFTS - INPUT	1	STRAIGHT KEYED, SAE "A" MODIFIED 0.75 X 1.75 LG
SEALS	S	BUNA N, STANDARD
PUMP DESIGN NUMBER	-21	221
CONTROL TYPE	- CM7	LOW RANGE PRESSURE COMPENSATOR 70 BAR
CONTROL OPTIONS	-	WITHOUT ADJUSTABLE MAXIMUM DISPLACEMENT STOP (STANDARD)
CONTROL DESIGN	-12	O-RING SEAL DESIGN
SPECIAL FEATURES	-	NONE

<http://www.eatonpowersource.com/products/configure/pumps/details/02-341687/>