



| | | |
|---------------------------|-----------------|------------------|
| Product no: 10_365_1905 | | |
| Max working pressure: | 350 | bar connected |
| | 350 | bar disconnected |
| Min burst pressure: | 1200 | bar connected |
| | 1200 | bar disconnected |
| Sealing material: | NBR | |
| Temperatur range: | -30 C - +100  C | |
| Nominal flow diameter,DN: | 10 | mm |
| Connection | WEO 1/2" | |
| Connection stroke: | mm | |

| | | | |
|----------------|-----------------|---------------------------|---------------------------|
| 15 | 2 | Valve Sleeve | Steel, plated |
| 14 | 1 | Valve opener | Steel, Plated |
| 13 | 1 | Spring | Steel |
| 12 | 1 | Spring | Stainless steel |
| 11 | 1 | Ratchet sleeve | Steel, plated |
| 10 | 1 | Protection plug | LDPE |
| 9 | 1 | O-ring | NBR |
| 8 | 1 | O-ring | NBR |
| 7 | 1 | O-ring | NBR |
| 6 | 1 | O-ring | NBR |
| 5 | 5 | Locking hook | Hard.steel Fe/Zn 8 P1 T/N |
| 4 | 1 | Front part | Steel, Fe/Zn 8 P1 N |
| 3 | 1 | Backup ring | |
| 2 | 1 | Back-up ring | Hytrel |
| 1 | 1 | Back part | Steel, plated |
| Detalj Item | Antal Quant. | Ben  mning Description | Material Material |

| | | | | | | | | | | | | |
|--|------------------|-----|------------------------|---------|-------------------|---|----------------|---|---------------------|---|--------------|----------|
| | Skala Scale | 2:1 | Rit  d Drawn | CABJOER | Kontr. Checked | - | Godk. Appr. | - |   m nr. Alt. no. | - | Dat. Date | 13-11-21 |
| | Assembly drawing | | Ritning nr/Drawing No. | | | | 50_365_1905 | | Utg./Issue | | | AA |