



Product No.	109325202
Nominal flow \varnothing DN:	19 mm
Connection Stroke:	
Max WP Connected:	350 bar
Max WP Disconnected:	bar
Min BP Connected:	1200 bar
Min BP Disconnected:	bar
Temperature range:	-30°C - 100°C
Connection:	BSP 3/4" Female
Sealing material:	NBR/PUR
Hexagon:	

Item	Qty	Description	Material	Part Number
12	1	Kit Mounting Br.	Steel	109324938
11	1	Dust Cap		109321008
10	2	Plug for coupling DN12.5		099327067
9	1	Stop screw	Steel, plated	099320921
8	1	Washer BRB 6,4	Steel, FZB	099331414
7	2	Coupling G 3/4" (Multi-X insert DN19)		107651907
6	1	Lever assembly		109324952
5	1	Coupling Block 2x3/4"+2x1/2"	Aluminium, Plated	099327750
1	1	Lock in house Kit		109324992
2	1	Screw	Brass, Ni plated	099320908
3	1	Spring	Stainless Steel	093613200
4	1	Nut	Brass, Ni plated	099330808

	Scale	1 : 3	Drawn	EP	Checked	JoEr	Appr.	PMB	ECO	12400	Date	2019-02-28	
	Assembly Drawing 509325202										Issue	AC	Sheet

This document must not be copied, either completely or in part, without permission. Any infringement will have legal consequences ©

A3