



Product no: 10_932_5052

Max working pressure:	350 bar connected	- bar disconnected
Min burst pressure:	1200 bar connected	- bar disconnected
Sealing material:	NBR/PUR	
Temperatur range:	-30°C - +100 °C	
Nominal flow diameter, DN:	19 mm	
Connection	WEO 3/4"	
Connection stroke:	- mm	

6	2	Seal	
5	2	Plug, nipple block	
4	2	Nipple kit DN19	
3	1	Nipple block	10_764_6901
2	2	Front part	
1	1	Center bolt kit	10_932_4982
Detalj Item	Antal Quant.	Benämning Description	Reservdelsnr. Spare part no.

CEJN	Skala Scale	1:2	Ritad Drawn	MBa	Kontr. Checked	JoEr	Godk. Appr.	FR	Äm nr. Alt. no.	-	Dat. Date	120125
	Assembly drawing		Ritning nr./Drawing No.		50_932_5052		Utg./Issue		AA			

Denna handling förbehålls utan rätt medgivande delges annan. kopieras eller eljest obehörigen användas. Alla rättigheter förbehålls.
 Överträdelse härvid beivras med stöd av gällande lag. This document must not be copied, either completely or in part, without permission. All rights reserved.
 Any infringement will have legal consequences. werden. Zuwiderhandlungen werden gerichtlich verfolgt. Alle rechte vorbehalten.

